

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) UK Patent Application (19) GB (11) 2 272 389 (13) A

(43) Date of A Publication 18.05.1994

(21) Application No 9223120.8

(22) Date of Filing 04.11.1992

(71) Applicant(s)
Bespak Plc

(Incorporated in the United Kingdom)

Bergen Way, King's Lynn, Norfolk, PE30 2JJ,
United Kingdom

(72) Inventor(s)
John Robin Davison
Paul Barnes
Geoffrey Brace

(74) Agent and/or Address for Service
Bout Wade Tennant
27 Fumival Street, LONDON, EC4A 1PQ,
United Kingdom

(51) INT CL⁵
B05B 11/02, A61M 15/00, B05B 17/06



(52) UK CL (Edition M)
B2F FFC F120 F204 F324
A5T TBE TDC

(56) Documents Cited
None

(58) Field of Search
UK CL (Edition L) A5T TBE TDC, B2F FFC
INT CL⁵ A61M 15/00, B05B 11/02 17/06
ONLINE DATABASE: WPI

(54) Dispensing apparatus

(57) A dispensing apparatus (1) defines an outlet (3) through which a metered dose of liquid (19) from a reservoir (16) is dispersed as an atomised spray. A droplet (19) of liquid is metered onto a perforate membrane (6) which is vibrated by means of a piezo electric transducer (10) such that atomised droplets are dispensed through the holes (7) formed in the membrane. At each actuation of a delivery means (14) which provides the metered quantity of liquid, the transducer is actuated so as to vibrate the membrane for a period greater than the dispensing period required for the droplet to be dispensed. The apparatus is particularly suitable for dispensing pharmaceutical preparations.



GB 2 272 389 A

FIG. 1.





FIG. 4.

3/5




FIG. 6.





FIG. 5



5/5
FIG. 7.





FIG. 8.



"DISPENSING APPARATUS"

This invention relates to dispensing apparatus for dispensing liquid as an atomised mist and in particular but not exclusively for dispensing medicaments for inhalation therapy.

It is known from GB-2240494A to provide dispensing apparatus in which a perforate membrane is vibrated such that liquid in contact with a rear face of the membrane is dispensed from a front face of the membrane as an atomised mist or spray. It is proposed that in the disclosed apparatus a predetermined dose is delivered by operation of a control circuit which regulates the dispensing period during which the membrane is vibrated, the supply of liquid being contained in a chamber of which the membrane constitutes a front wall.

A disadvantage of such an arrangement is that when not in use the liquid within the chamber is open to air through holes in the perforate membrane and may thereby be subject to evaporative losses or become bacteriologically contaminated or otherwise degraded.

A further disadvantage of such an arrangement is that variation in the rate at which liquid is dispensed through the membrane as a mist will result in variation in the total quantity delivered during the dispensing period.

According to the present invention there is disclosed dispensing apparatus comprising a housing defining a dispensing outlet, a perforate membrane having a front face exposed at the outlet and a rear face contacted in use by liquid to be dispensed, vibrating means connected to the housing and operable to vibrate the membrane to dispense droplets of the liquid through the membrane, liquid supply means connected to the housing and delivery means operable

at successive actuations of the delivery means to deliver a respective metered quantity of the liquid from the liquid supply means into contact with the rear face of the membrane whereby in use a metered
5 quantity of liquid is dispensible at the outlet by operation of the vibrating means for an operating period greater than the dispensing period required for the metered quantity to be dispensed through the membrane.

10 An advantage of such apparatus is that it facilitates the dispensing of all of the liquid coming into contact with the rear face of the membrane as a single dose. It is thereby possible to avoid contact between liquid and ambient air during periods of
15 non-use between successive actuations. For pharmaceutical preparations this is particularly important since it may obviate the need for the use of preservatives in the liquid and avoids evaporative losses.

20 The liquid supply means conveniently comprises a pipette and the delivery means comprises a piston movably mounted in the pipette to displace liquid therefrom and indexing means operable to move the piston at successive actuations through a respective
25 distance to thereby displace a metered quantity of liquid.

Alternatively the liquid supply means may comprise a reservoir containing liquid and the delivery means may comprise a metering pump connected
30 to the reservoir, the metering pump comprising a cylinder defining a chamber and a piston reciprocatably mounted in the cylinder to displace a metered volume of liquid from the chamber at each actuating stroke.

35 Alternatively the delivery means may comprise an electrically driven pump operable to deliver a flow of

liquid and control means operable to turn the pump on and to turn the pump off after delivery of the metered volume of liquid.

5 In an alternative apparatus the liquid supply means comprises a pressurised dispensing container within which a supply of liquid is maintained under pressure and the delivery means comprises a metering valve operable to release from the container a metered volume of the liquid.

10 In a further alternative apparatus the liquid supply means comprises a plurality of cells each containing a metered volume of liquid and the delivery means comprises a dispensing station operable to release at each actuation thereof the contents of a
15 respective cell.

Preferably the housing comprises an annular member connected peripherally to the vibrating means and defining a central aperture overlaid by the membrane.

20 Preferably the annular member comprises an upper surface which is concave so as to be downwardly sloping in a radially inward direction when the apparatus is held in use in a preferred operating orientation.

25 Advantageously the upper surface of the annular member is formed of a liquid repellant material. A liquid droplet deposited on the upper surface is thereby encouraged to move radially inwardly into contact with the membrane.

30 Conveniently the annular member comprises a radially innermost surface portion defining the aperture and co-operating with the membrane to define a well for receiving in use a droplet of liquid to be dispensed.

35 The housing may define a duct communicating between an air inlet and an outlet port, the

dispensing outlet being located in the duct intermediate the air inlet and the outlet port such that the front face of the membrane is exposed to air within the duct.

5 The outlet port may be an inhalation port for oral or nasal use.

 Such an arrangement is useful in the administration of inhaled pharmaceutical liquid products where it is required for an atomised spray of
10 liquid to be entrained in an inhaled air flow passing through the duct.

 Apparatus in accordance with the present invention may be provided with an air impeller connected to the housing so as to be operable to
15 create a flow of air through the duct from the air inlet to the outlet port.

 Such an arrangement may be used for dispensing cosmetics and perfumes. A further application of such an arrangement is ophthalmic use where an
20 ophthalmic preparation can be used to generate an atraumatic mist which is administered to the user's eye by means of an eye cup provided in the housing so as to communicate with the duct.

 Particular embodiments of the present invention will now be described by way of example only and with reference to the accompanying drawings of which:-

 Figure 1 is a schematic sectioned elevation of a first apparatus in accordance with the present invention;

30 Figure 2 is a schematic sectioned elevation of an alternative apparatus having a pipette with an indexing mechanism;

 Figure 3 is a schematic sectioned elevation of a further alternative apparatus having a metering pump;

35 Figure 4 is a schematic sectioned elevation of a further alternative apparatus having an electrically

driven pump;

Figure 5 is a schematic sectioned elevation of a further alternative apparatus having a pressurised dispensing container with a metering valve;

5 Figure 6 is a schematic sectioned elevation of a further alternative apparatus in which the liquid supply means comprises a plurality of cells whose respective contents are released during successive actuations at a dispensing station;

10 Figure 7 is a schematic sectioned elevation of a further alternative apparatus for use in dispensing an ophthalmic preparation; and

15 Figure 8 is a schematic sectioned elevation of a further alternative apparatus having an air impeller for dispensing cosmetic preparations.

In Figure 1 a first apparatus 1 has a housing 2 defining an outlet 3. The housing 2 includes an annular member 4 defining a central aperture 5 which is overlaid by a perforate membrane 6.

20 The membrane 6 is peripherally bonded to the annular member 4 so as to close the aperture 5 and defines an array of holes 7 of 3 microns diameter and 25 microns spacing.

25 The annular member 4 extends horizontally such that a front face 8 of the membrane 6 is downwardly oriented and a rear face 9 of the membrane is upwardly directed.

30 The annular member 4 extends radially with uniform thickness into contact with an annular piezoelectric transducer 10 which is connected to an oscillator circuit 11 (not shown) operable to energise the transducer. The transducer 10 is arranged such that vibration is applied at right angles to the plane of the annular member 4 such that transverse acoustic waves are propagated radially inwardly of the annular member so

35

as to excite the membrane 6 in an axial direction i.e. producing vertical movement of the membrane.

5 The membrane 6 is bonded to a lower surface 11 of the annular member 4 such that, because of the finite thickness of the member at the aperture 5, a shallow well 12 is defined in the aperture 5 above the membrane 6 and bounded radially by an inner vertical annular face 13 of the annular member 4.

10 A delivery means 14 is located within the housing 2 and is operable by means of an actuator 15 to deliver at each actuation a metered volume of liquid from a liquid supply means 16, the liquid being delivered through a delivery tube 17 to a delivery location 18 immediately adjacent and above the
15 membrane 6.

A droplet of liquid 19 is shown located on top of the membrane 6 within the well 12 immediately following actuation of the delivery means 14 to dispense a metered volume of 20 microlitres of liquid,
20 the membrane being vibrated to produce an atomised spray 20 in the air surrounding the outlet 3.

In use, the membrane 6 is initially free from liquid and a metered volume is dispensed by actuation of the delivery means 14 such that a droplet of liquid
25 is placed in the well 12. The vibrating means is then actuated and continues to vibrate the membrane 6 for an operating period determined by a timer (not shown).

30 The operating period is selected to be greater than the dispensing period required to dispense all of the liquid contained in the droplet 19 as an atomised spray or mist through the membrane holes 7.

Since in practice the dispensing period required to totally dispense a metered volume will vary from
35 actuation to actuation, the operating period is selected to be sufficiently greater than the average

dispensing period in order to accommodate such variation thereby ensuring that the quantity of liquid dispensed is independent of the rate at which the liquid flows through the membrane.

5 The vibrating means is then de-actuated until further use is required.

10 An alternative apparatus 30 shown in Figure 2 will now be described using corresponding reference numerals to those of Figure 1 where appropriate for corresponding elements.

15 The second apparatus 30 includes a housing 2 with an annular member 4 supporting a membrane 6 for vibration by actuation of a transducer 10. The annular member 4 has an upper surface 31 which is concave and downwardly sloping in a radially inward direction so that the aperture 5 is located at the lowest part of the surface 31 thereby assisting draining of any liquid on the upper surface 31 into the well 12.

20 The upper surface 31 is coated with a liquid repellant surface to assist this draining action and ensure that any droplet of liquid deposited on the upper surface finds its way into contact with the membrane 6.

25 The housing 2 defines a horizontally extending cylindrical duct 32 communicating between an air inlet 33 and an inhalation port 34 suitable for oral inhalation. The outlet 3 is located intermediate the inlet 33 and the inhalation port 34 so as to communicate with the duct 32, the membrane 6 having a front face 8 which is directly exposed to air within the duct 32.

30 The second apparatus 30 has a delivery means 14 comprising a pipette 35 within which a piston 36 is advanceable by means of an indexing mechanism 37 in discrete measured steps so as to displace metered

volumes of liquid 38 from the pipette. A delivery tube 17 communicates between the pipette 35 and a delivery location 18 so as to dispense a metered quantity of the liquid into contact with the membrane 6 at each actuation of the indexing mechanism 37.

In use the indexing mechanism is actuated to deliver a drop into the well 12 and the vibrating means is then actuated. Vibration of the membrane 6 discharges a fine mist 20 of droplets into the duct 32 until such time as the liquid within the well is entirely consumed. The mist is entrained in an air flow within the duct when the user inhales air through the inhalation port 34 such that the liquid is orally administered for inhalation into the user's lungs.

A third apparatus 40 is shown in Figure 3 and will now be described using corresponding reference numerals to those of preceding Figures where appropriate for corresponding elements.

The third apparatus 40 includes a housing 2, annular member 4 and duct 32 of the type described above with reference to the second apparatus 30 in Figure 2. The third apparatus 40 differs in that the delivery means 14 is a manually actuated metering pump 41 which has a cylinder 42 receiving a piston 43 actuated by means of an actuator 44. At each actuation a single stroke of the piston 43 displaces from the cylinder 42 a metered quantity of liquid which flows through a one-way outlet valve 45 into delivery tube 17. The piston then returns to its rest position and the chamber is refilled for further operation. The cylinder 42 and piston 43 are shown schematically in Figure 3 and not to scale, the appropriate stroke and metered volume in a practical arrangement being selected to dispense a drop of liquid at each actuation.

Liquid is supplied to the pump 41 from a

reservoir 46 via an inlet valve 47, the reservoir being of sufficient capacity to contain a large number of metered volumes of liquid.

5 In use the metering pump 41 is actuated by manual depression of the actuator 44 and a single stroke of the piston 43 displaces a droplet of liquid on to the membrane 6 via the delivery tube 17.

10 The transducer 10 is then actuated so as to vibrate the membrane and dispense atomised droplets into the duct 32 from where they are inhaled by the user via the inhalation port 34. After a time period sufficient for the droplet to be consumed the transducer 10 is de-actuated and the apparatus is ready for further use.

15 A fourth alternative apparatus 50 shown in Figure 4 will now be described using corresponding reference numerals to those of preceding Figures where appropriate for corresponding elements.

20 The apparatus 50 is generally similar to the third apparatus 40 of Figure 3 but includes an electrically operated pump 51 which is operable to deliver liquid from a reservoir 46 to a delivery location 18 when energised by a controller circuit 52.

25 The pump 51 is a peristaltic pump providing a continuous output flow when energised and the controller circuit 52 achieves delivery of a measured volume by controlling the duration for which pump 51 is energised.

30 Once a metered volume of liquid has been delivered on to the membrane 6 the operation of the apparatus 50 corresponds to that of the third apparatus 40 described above.

35 A fifth apparatus 60 shown in Figure 5 will now be described using corresponding reference numerals to those of preceding Figures where appropriate for corresponding elements.

The fifth apparatus 60 includes a housing 2 with an annular member 4 supporting membrane 6 of the same general type as those described above with reference to Figures 2, 3 and 4. A quantity of liquid is
5 contained within a pressurised dispensing container 61 of a type commonly utilised in aerosol dispensers. The container 61 has a metering valve 62 operable to dispense a metered volume of liquid through a tubular stem 63 in response to depression of the stem 63
10 relative to the container 61.

The stem 63 is received within a socket 64 fixed to the housing 2 and the container 61 is displaceable relative to a tubular sheath 65 extending upwardly of the housing so as to provide relative movement between
15 the container and the stem 63 thereby enabling the metering valve 62 to be actuated by manual depression of the container 61 relative to the housing 2.

The socket 64 defines a delivery orifice 66 communicating with the stem 63 and through which the
20 liquid is dispensed on to the membrane 6.

In use the membrane is vibrated by actuation of the transducer 10 for a period sufficient to totally atomise a droplet of liquid received within the well 12 so that a fine mist can be orally inhaled via the
25 duct 32.

A sixth apparatus 70 is shown in Figure 6 and will now be described using corresponding references to those of preceding Figures where appropriate for corresponding elements.

30 The sixth apparatus 70 includes a housing 2, an annular member 4 and a membrane 6 of the type disclosed with reference to Figures 2 to 5. A delivery means 14 comprises a liquid supply means 71 in which metered quantities of liquid are contained
35 within individual cells 72. The cells 72 are fed in turn to a dispensing station 73 which is operable by

depression of an actuator 74 to release the contents of a cell and conduct the contents of the cell via delivery tube 17 on to the membrane 6.

5 The cells 72 comprise gelatin capsules formed on a disposable strip 75 which is fed to the dispensing station 73 where the capsules are ruptured by action of the actuator 74 during each dispensing operation.

10 A seventh apparatus 80 is shown in Figure 7 and will now be described using corresponding references to those of preceding Figures where appropriate for corresponding elements.

The seventh apparatus 80 is based on the second apparatus 30 of Figure 2 but includes a modified housing 81 in which the inhalation port 34 of Figure 2 is replaced by an eye cup 82 and air inlet 33 is provided with an air impeller 83.

20 The air impeller 83 consists of a fan 84 driven by an electric motor 85 so as to create a flow of air along duct 32 and air release holes 86 are provided adjacent to the eye cup 82 to allow the escape of air peripherally of the eye cup.

The seventh apparatus 80 is operable to dispense an aerosol mist into the duct 32 in the same manner as the second apparatus 30 of Figure 2. The product
25 dispensed as a liquid is an ophthalmic preparation providing an atraumatic mist delivered to the user's eye 87 when engaged with the eye cup 82.

30 An eighth apparatus 90 is shown in Figure 8 and will now be described using corresponding references to those of preceding Figures where appropriate for corresponding elements.

The eighth apparatus 90 is based on the first apparatus 1 of Figure 1 but includes a modified housing 91 which defines a cylindrical duct into which
35 the outlet 3 opens to release an atomised spray in use. The duct 92 has an outlet 93 through which air

emerges when a flow of air through the duct 92 is created by an air impeller 83 located in the air inlet 33. The air impeller 83 comprises a fan 84 driven by an electric motor.

5 The eighth apparatus 90 is primarily intended for dispensing cosmetic preparations, perfumes and fragrances.

10 The apparatus shown in Figure 1 may be used in applications other than for medical inhalation therapy such as to dispense cosmetic preparations including perfume.

15 The apparatus of Figures 2 to 6 is suitable for inhalation therapy and may in each case be modified to include an inhalation sensor in order to synchronise the release of droplets through the membrane with inhalation by the user. The inhalation port may be adapted for oral or nasal inhalation.

20 The fourth apparatus shown in Figure 4 with reference to a peristaltic pump may alternatively use a piezoelectric micro pump of the type disclosed in EP-0398583A in which a diaphragm is reciprocated by action of a piezoelectric transducer.

25 The seventh apparatus 80 of Figure 7 may alternatively be provided with a metering pump of the type disclosed with reference to Figure 3 or Figure 4 or alternatively may utilise the pressurised dispensing container 61 and metering valve 62 of the fifth apparatus shown in Figure 5. Alternatively the liquid supply means 71 of Figure 6 may be utilised in
30 the seventh apparatus 80.

 Similar comments apply to the eighth apparatus 90 where similarly alternative arrangements may be utilised to deliver a droplet on to the membrane 6.

35 The air impeller 83 utilised in Figures 7 and 8 may be replaced by an equivalent arrangement such as a mechanically driven fan or bellows arrangement.

The fifth apparatus 70 may alternatively be used with different types of package defining individual cells. For example a plastic, aluminium or laminated strip may be formed so as to define pockets each
5 defining a cell containing a pre-measured quantity of liquid, each pocket being closed by a second strip of plastic, aluminium foil or a laminate. The liquid may then be released by piercing the pocket or by peeling off the second strip.

10 In the configuration shown in Figure 6, individual metered quantities of liquid are placed in the packaging at the time of manufacture. Each dose is consumed at each actuation of the dispensing apparatus. This arrangement has the advantage of
15 providing for different doses to be administered by the apparatus by providing a range of packaged doses of predetermined volume from which the required dose can be selected or prescribed as may be required.

The frequency vibration of the membrane
20 described above with reference to each of the embodiments may be selected to any suitable value, preferably in the kilohertz to megahertz range.

The pressurised dispensing container of Figure 5 may be of the conventional type in which an evaporable
25 propellant is mixed with a liquid product or of an alternative type such as a container adapted to dispense under pressure from a compressed gas. The liquid product may be contained separately from the propellant liquid or gas within a collapsible bag or
30 compartment.

CLAIMS:

1. Dispensing apparatus comprising a housing
defining a dispensing outlet, a perforate membrane
5 having a front face exposed at the outlet and a rear
face contacted in use by liquid to be dispensed,
vibrating means connected to the housing and operable
to vibrate the membrane to dispense droplets of the
liquid through the membrane, liquid supply means
10 connected to the housing and delivery means operable
at successive actuations of the delivery means to
deliver a respective metered quantity of the liquid
from the liquid supply means into contact with the
rear face of the membrane whereby in use a metered
15 quantity of liquid is dispensible at the outlet by
operation of the vibrating means for an operating
period greater than the dispensing period required for
the metered quantity to be dispensed through the
membrane.

20

2. Dispensing apparatus as claimed in claim 1
wherein the liquid supply means comprises a pipette
and the delivery means comprises a piston movably
mounted in the pipette to displace liquid therefrom
25 and indexing means operable to move the piston at
successive actuations through a respective distance to
thereby displace a metered quantity of liquid.

3. Dispensing apparatus as claimed in claim 1
30 wherein the liquid supply means comprises a reservoir
containing liquid and the delivery means comprises a
metering pump connected to the reservoir, the metering
pump comprising a cylinder defining a chamber and a
piston reciprocatably mounted in the cylinder to
35 displace a metered volume of liquid from the chamber
at each actuating stroke.

4. Dispensing apparatus as claimed in claim 1
wherein the liquid supply means comprises a reservoir
and the delivery means comprises an electrically

5 driven pump operable to deliver a flow of liquid and
control means operable to turn the pump on and to turn
the pump off after delivery of the metered volume of
liquid.

10 5. Dispensing apparatus as claimed in claim 1
wherein the liquid supply means comprises a
pressurised dispensing container within which a supply
of liquid is maintained under pressure and the
delivery means comprises a metering valve operable to
15 release from the container a metered volume of the
liquid.

20 6. Dispensing apparatus as claimed in claim 1
wherein the liquid supply means comprises a plurality
of cells each containing a metered volume of liquid
and the delivery means comprises a dispensing station
operable to release at each actuation thereof the
contents of a respective cell.

25 7. Dispensing apparatus as claimed in any
preceding claim wherein the housing comprises an
annular member connected peripherally to the vibrating
means and defining a central aperture overlaid by the
membrane.

30

 8. Dispensing apparatus as claimed in claim 7
wherein the annular member comprises an upper surface
which is concave so as to be downwardly sloping in a
radially inward direction when the apparatus is held
35 in use in a preferred operating orientation.

9. Dispensing apparatus as claimed in claim 8 wherein the upper surface of the annular member is formed of a liquid repellant material.

5 10. Dispensing apparatus as claimed in any of claims 8 to 9 wherein the annular member comprises a radially innermost surface portion defining the aperture and co-operating with the membrane to define a well for receiving in use a droplet of liquid to be
10 dispensed.

11. Dispensing apparatus as claimed in any preceding claim wherein the housing defines a duct communicating between an air inlet and an outlet port,
15 the dispensing outlet being located in the duct intermediate the air inlet and the outlet port such that the front face of the membrane is exposed to air within the duct.

20 12. Dispensing apparatus as claimed in claim 11 wherein an air impeller is connected to the housing so as to be operable to create a flow of air through the duct from the air inlet to the outlet port.

25 13. Dispensing apparatus as claimed in claim 12 wherein the housing defines an eye cup communicating with the duct.

14. Dispensing apparatus as claimed in claim
30 11 wherein the outlet port comprises an inhalation port for oral or nasal use.

15. Dispensing apparatus as claimed in any preceding claim comprising a timer connected to the
35 vibrating means and operable to determine the operating period during which the vibrating means is

actuated and wherein the operating period is selected to be greater than the dispensing period required for the metered quantity to be dispensed through the membrane.

5

10

15

20

25

30

35

Relevant Technical fields

(i) UK CI (Edition L) B2F (FFC) ; A5T (TBE, TDC)

(ii) Int CI (Edition 5) B05B 11/02, 17/06;
A61M 15/00

Databases (see over)

(i) UK Patent Office

(ii) ONLINE DATABASE: WPI

Search Examiner

S I AHMAD

Date of Search

28 JANUARY 1993

Documents considered relevant following a search in respect of claims 1-15

Category (see over)	Identity of document and relevant passages	Relevant to claim(s)
	None	

Category	Identity of document and relevant passages 19	Relevance to claim

Categories of documents

X: Document indicating lack of novelty or of inventive step.

Y: Document indicating lack of inventive step if combined with one or more other documents of the same category.

A: Document indicating technological background and/or state of the art.

P: Document published on or after the declared priority date but before the filing date of the present application.

E: Patent document published on or after, but with priority date earlier than, the filing date of the present application.

&: Member of the same patent family, corresponding document.

Databases: The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).